

BE ZW25 UVS C 2xSOLAR 4 ZR R1

Preflex UVS 25mm 2 x SOLAR H1Z2Z2-K 4mm BLA R C100

Properties of the article

◦ Articlenumber	1234003314
◦ Barcode	5420056286824
◦ Category	Solar
◦ Gross weight (kg)	20.895
◦ Dimensions (WxLxH)	500 x 500 x 200 MM
◦ Packaging	Roll
◦ Length	100

Properties of the Preflex® tube

◦ Material of tube	Halogen-free Polypropylene
◦ Color	Black
◦ Outer diameter (mm)	25
◦ Inner diameter (mm)	18.3
◦ Classification	ICTA 3422
◦ Pressure resistance	750N / 23°C
◦ Impact resistance	6J / -5°C
◦ Breakthrough test	2000V / 50-60 Hz 15min.
◦ Insulation resistance	min. 100 Mohm/80cm
◦ Test temperature	-5°C tot +90°C
◦ Min. installation temperature	-5°C

Characteristics of the cable or cable combination

◦ Cable type	SOLAR 4	SOLAR 4
◦ Color		
◦ Insulation	LSOH	
◦ CPR Class	cca s2 d2 a2	

Certificates

◦ Norm van de buis	EN 61386-1, EN 61386-22, EN 60423; EN 61034, EN 60754-1, EN 60754-2
◦ Norm van de kabel	HD 60 364 EN 50618: 2014

Certificates

